

Watchman Gospel Signs

Instructions for applying vinyl (hinge method)

1. Clean area thoroughly with rubbing alcohol.
2. Center letters on vehicle with transfer tape and waxed backing still attached. Be sure to measure from the letters themselves (rather than to the edge of the backing) to make sure the sign is straight and centered.
3. Temporarily attach the vinyl letters to the vehicle with one long piece of masking tape (the hinge), from top to bottom, centered right to left on the sign.
4. Fold back all three layers (transfer tape, letters, and waxed backing) back across the tape, peel away backing, and cut off as much backing as you can (approx. ½ of it) without removing the masking tape hinge.
5. Starting from the tape hinge, smooth the transfer tape and letters down onto sign. Rub hard (preferably with a rigid straight edge such as a credit card) to remove air bubbles and make sure the letters are stuck fast to sign.
6. Remove masking tape hinge and fold back other half of letters. Remove vinyl backing and repeat above process.
7. When letters have been thoroughly smoothed onto sign, carefully remove transfer tape and discard.
8. HINT: In step 4, if you are putting the letters on a curved window, it might help to cut the sign into 2 or 3 strips (without removing the tape hinge) and put it on 1 strip at a time.
9. If you run into trouble, PANIC for about 5 minutes or so. Or you could call Roger at 541-517-7577. God bless!